

ViziPrint®

Deco +

This optically clear printable window film utilises a special ink-receptive top coat for greater adhesion of inks. ViziPrint® Deco + is ideal for architectural applications where decorative glass details are needed to create dynamic spaces, including conference rooms or private meeting areas. It can also be used to create graphics and window decals for retail storefronts and POP or backlit displays.

- IDEAL FOR HIGH QUALITY GRAPHICS FOR HIGH END RETAIL STOREFRONTS
- SUITABLE FOR CONFERENCE ROOMS AND ARCHITECTURAL APPLICATIONS.

Product Code: VPDP

70
micron

Optically
Clear
PET

Gloss



UV
Latex



Clear
Permanent
Acrylic (Pressure Sensitive)



Width 1524mm

YEARS DURABILITY
7

INTERIOR

YEARS DURABILITY
3

EXTERIOR

CREATE ARCHITECTURAL APPLICATIONS



APPLICATIONS

- Smooth Flat Surfaces
- Retail Backlit Displays
- Window Graphics
- Decals & Stickers

Certified for
HP Latex Inks

This media may not be certified for all HP Latex ink and printing systems. Please check the HP media locator website at hp.com/go/mediasolutionslocator

DRYTAC®

ADHESIVE SCIENCE

www.drytac.com

ViziPrint®

Deco +

ViziPrint® Deco + is a 70µ (2.8 mil) optically clear gloss PET film, coated with a permanent clear acrylic adhesive and protected by an opaque siliconised PET release liner that has a super smooth profile to enhance the clarity when applied to glass. It has a special top coat to enhance the adhesion of inks. The film's high quality adhesive adheres to most substrates.

- IDEAL FOR HIGH QUALITY GRAPHICS FOR HIGH END RETAIL STOREFRONTS
- SUITABLE FOR CONFERENCE ROOMS AND ARCHITECTURAL APPLICATIONS.

INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application. Use gloves to avoid fingerprints. Wet installation is recommended.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2021 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Gloss Optically Clear PET with Ink-Receptive Top Coat
Adhesive	Clear Permanent Acrylic (Pressure Sensitive)
Release Liner	Siliconised 1 Side PET

PRODUCT CHARACTERISTIC

Film Thickness	2.8 mil (70µ)
Adhesive Layer	0.8mil (20µ)
Film/Adhesive Ratio	2.8:0.8
Outdoor Durability	3 Years
Fire Rating	Class B1 (DIN 4102-1)
Application Temperature	>41°F (5°C)
Service Temperature Range	-4°F to 266°F (-20°C to 130°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

DRYTAC®

ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com