

SpotOn®

SPOW54098 - DryTac Spot On 200 Floor Graphic

Floor 200

SpotOn® Floor 200 is a print media for short-term, indoor floor graphics without the need for lamination. It boasts a post-printed R-10 anti-slip rating, which allows for vibrant, slip-resistant floor graphics. SpotOn® Floor 200 has been specifically developed for a simple, easy and tool-free installation. Thanks to a unique dot-pattern printed pressure-sensitive polyacrylate adhesive, this film can be applied to multiple flooring surfaces including short pile carpets, floor or ceramic tiles, sealed wood, concrete, waxed vinyl, marble, terrazzo surfaces and more. It can also be cleanly and quickly removed within six months of application.

- IDEAL FOR SHORT TERM INDOOR FLOOR APPLICATIONS
- EASY TOOL FREE APPLICATION
- CAN BE REMOVED EASILY WITHIN 6 MONTHS

Product Code: SPOW

200 White Monomeric PVC
micron

Matte



(Eco)Solvent**
Latex
UV



DOT Pattern
Polyacrylate
Adhesive



Widths up to 1370mm



6 MONTHS DURABILITY
INTERIOR*

SLIP-CERTIFIED WITHOUT LAMINATION



APPLICATIONS

APPLIED TO FLOOR,
CERAMIC TILES,
SEALED WOOD,
CONCRETE, WAXED VINYL,
SHORT PILE CARPETS***



Certified for
HP Latex Inks



DRYTAC®
ADHESIVE SCIENCE

FLOOR 200

TECHNICAL SPECIFICATION

SpotOn® Floor 200 is a 200µ (8 mil) embossed printable white matte monomeric PVC film, coated on one side with a dot-pattern, removable pressure sensitive polyacrylate adhesive. The adhesive is protected by a single sided, siliconised clay coated kraft release liner. This high quality ink receptive embossed white vinyl was specifically developed for easy application. SpotOn® Floor 200 has a post-printed anti-slip rating of R10, according to DIN 51130:2010, which allows for vibrant, slip resistant floor graphics without the need for lamination.

- EASY TOOL & BUBBLE FREE APPLICATION
- CAN BE REMOVED EASILY WITHIN 6 MONTHS

* Up to 6 months indoor durability dependent upon floor-traffic and correct installation.

***If installed to carpet, the carpet installation surface must be short pile or tightly woven, minimal texture with a limited cushion. The carpet should be clean and dry prior to application. Due to the huge variance of carpet surfaces, materials and types along with pre and post chemical treatments, a test sample is mandatory prior to production and installation. It is important that all printer and ink manufacturer guidelines are followed. The Drytac limited warranty only covers for material defect, no returns or consequential losses will be accepted.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

PRODUCT STRUCTURE

Film	White Matte Monomeric PVC
Adhesive	Dot-Pattern Removable Polyacrylate
Release Liner	140 gsm 1 Side Siliconised PE Coated Kraft

PRODUCT CHARACTERISTIC

Film Thickness	8 mil (200µ)	} 8.6 mil (215µ)
Adhesive Layer	0.6 mil (15µ)	
Outdoor Durability	Internal Use Only	
Application Temperature	>41°F (5°C)	
Service Temperature Range	-4°F to 149°F (-20°C to 65°C)	
Slip Rating (Post Printed)	R10 (DIN 51130:2010) Low Slip Potential (EN 13036-4)	
Fire Rating (DIN 4102-1)	B1 Rating	
Shelf Life	2 years	
Storage Conditions	64°F to 77°F (18°C to 25°C); 40 - 65% Relative Humidity	

**PRINTING RECOMMENDATIONS
UV and Latex inks offer the greatest durability for floor applications. Due to the variance of solvent inks it is recommended scuff resistance is tested prior to installation.



DRYTAC
ADHESIVE SCIENCE

Johannesburg

Unit 21, Hylauma Street,
Fern Towers, Ferndale,
Randburg, Gauteng
South Africa
consumables@midcomp.co.za
Tel: +27 (0) 10 020 9999

Cape Town

Unit 1, 4 Platinum Close,
Phoenix, Cape Town
Western Cape,
South Africa
cptorders@midcomp.co.za
Tel: +27 (0) 21 552 3453

Durban

Unit 1, Janic Park,
30 Moreland Drive, Redhill
Durban, Kwa-Zulu Natal,
South Africa
consumables@midcomp.co.za
Tel: +27 (0) 10 020 9999