



HP Removable Adhesive Fabric



The HP large format printing system—the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



¹ As of the date of this document, this product does not contain any of the chemicals on the EU's Candidate List for Authorization (otherwise known as Substances of Very High Concern) in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Article 33 Declaration published at [HP Printing Products and Consumable Supplies](#).

² Class A, ASTM E84 approved fire certifications.

³ Recommended on indoor smooth, non-porous, sealed flat and dry surfaces for up to 3 months. Slip resistance for dry environments based on testing by Sotter Engineering Corporation, June 2020, according to [ANSI A137.1/A326.3](#) and [AS HB198:2014 \(AS/NZS 4586\)](#).

Print high-quality, repositionable graphics that stick to non-porous surfaces

Easy-to-install, reposition, and remove

Enjoy the ease of working with this repositionable adhesive-back fabric that is easy to install, reposition, and remove with virtually no residue. The special adhesive is designed to stick to non-porous surfaces to create seamless, photographic image quality wall and floor graphics. Tested and approved for indoor smooth floor graphics.³

Reduce the environmental impact of printing

Offer an adhesive fabric that complies with high health standards. Help meet environmental and safety objectives with this REACH compliant,¹ flame-resistant,² adhesive fabric.

Grab attention with vibrant image quality for a variety of applications

Capture realistic graphic detail for applications from wall murals and event signage to retail displays. Achieve a high-quality look with this versatile, easy-to-handle, repositionable self-adhesive fabric—ideal for a wide range of indoor and outdoor applications.

Target customers	Applications	Benefits
Print service providers	Wall murals	Designed for easy installation, repositioning, and removal without wrinkles or tearing for a wide range of applications
Government agencies	Wall cut-outs	Ability to contour cut and apply without stretching
Graphic artists	Indoor and short-term outdoor signage	Smooth, matte finish for deep blacks, vivid colors, and high ink saturation
Sign shops	Point-of-purchase displays	Outstanding photographic image quality
Retail	Trade show graphics	Class A, ASTM E84 flame resistance ²
	Decals	REACH compliant ¹
	Window graphics	Compatible with Original HP Bright Office Inks, HP Vivid Photo Inks, HP PageWide XL and HP Latex Inks
	Floor graphics	Slip resistant for floor graphics ³



Technical specifications

HP Removable Adhesive Fabric

For the latest ICC profiles/paper presets, please visit HPLFMedia.com/hp/paperpresets.

Ink technology	HP Bright Office Inks, HP Vivid Photo Inks, HP PageWide and HP Latex Inks			
Material	Polyester fabric			
Weight (With liner)	289 g/m ² per ISO 536 Test Method			
Thickness (With liner)	304 microns/12 mil per ISO 20534 Test Method			
Liner	120 g/m ² , double-sided PE-coated silicone paper			
Adhesive	Clear, removable, and repositionable adhesive			
Removability	Up to 3 years removable/repositionable indoors			
Opacity	Greater than 85% per TAPPI T-425 Test Method and ISO 2471 Test Method			
Brightness	Greater than 87% per TAPPI T-452 Test Method			
Whiteness	118 per ASTM E313-98 Test Method			
Finish	Matte			
Slip rating	Certified according to ANSI A137.1/A326.3 and AS HB198:2014 (AS/NZS 4586) ⁷			
Operating temperature	15 to 25° C / 59 to 77° F			
Operating humidity	20 to 80% RH			
Water resistance	Moderately water-resistant ⁴			
Wind orientation	Print side out			
Core size	3-in core with a removable 2-in core adapter			
Dry time	Immediate			
Flame resistance	Class A, ASTM E84 ⁵			
Lamination	For additional protection, liquid or spray coatings are recommended			
PageWide Cutter	The weight of this material is higher than the recommended weight limit for the HP PageWide XL cutter, which may reduce the expected life of the cutter			
Shelf life	1 year, unopened in original packaging			
Storage temperature	10 to 27° C / 50 to 80° F			
Storage humidity	35 to 65% RH			
Environmental	REACH compliant ⁶			
Finishing/post processing	Use a carbide knife for kiss and die cutting			
Installation tip	To install the graphic, peel 101 millimeters (4 inches) of the release liner off the graphic and place on wall or surface. Continue to peel back 101 millimeters (4 inches) of the liner incrementally while mounting.			
Country of origin	Product of China and Malaysia			
Ordering information	Product numbers	Roll sizes	UPC codes	Region
	8SU04A	610 mm x 30,5 m (24 in x 100 ft)	848412025675	United States, Europe
	8SU05A	914 mm x 30,5 m (36 in x 100 ft)	848412025682	United States, Europe
	8SU06A	1067 mm x 30,5 m (42 in x 100 ft)	848412025699	United States, Europe
	8SU08A	1372 mm x 30,5 m (54 in x 100 ft)	848412025729	United States, Europe
	8SU09A	1524 mm x 30,5 m (60 in x 100 ft)	848412025736	United States, Europe
Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement, please see HPLFMedia.com/hp/MediaWarranties . To obtain warranty service, please contact BMG customer support at HPLFMedia.com/hp/en/contactus .			

⁴ Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see HPLFMedia.com/hp/printpermanence.

⁵ Class A, ASTM E84 approved fire certifications.

⁶ As of the date of this document, this product does not contain any of the chemicals on the EU's Candidate List for Authorization (otherwise known as Substances of Very High Concern) in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Article 33 Declaration published at [HP Printing Products and Consumable Supplies](#).

⁷ Slip resistance for dry environments based on testing by Sotter Engineering Corporation, June 2020, according to [ANSI A137.1/A326.3](#) and [AS HB198:2014 \(AS/NZS 4586\)](#).



For detailed information on the HP large format printing materials portfolio and to order, visit HPLFMedia.com

© 2020 HP Development Company, L.P. © 2020 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.

HP is a registered trademark of HP Development Company, L.P. and is used by Brand Management Group on license from HP Development Company, L.P.

