# HP Latex 800 W Printer



## Win high-value jobs with white ink and productive printing—and sharpen vour sustainability edge



## Expand into white, produce the highest value jobs

- Extend your portfolio into high-margin stickers and window graphics with the whitest white.
- Print white without complexity—automatic recirculation and printhead cleaning reduce manual purging.
- Deliver vivid colors at high speed, get striking contrast using pure blacks, and expect sharp 4-
- Choose from a wide application range covering banners/textiles/poster paper, canvas, wallpaper, and vinyl.

## Robust, smart, and productive printing

- Drive high productivity with saturated color at speeds up to 388 ft<sup>2</sup>/hr outdoor<sup>2</sup>, easy spindleless loading
- Control print operations virtually anytime, anywhere with HP PrintOS tools, and grow with HP Learn trainings.
- Work fast processing reprints and multi-copy jobs with a smart front panel, and store up to 100 iobs.
- Help reduce running costs with cost-effective 3liter HP ink cartridges, changed while the printer

## GO BEYOND—Lead with environmental certifications<sup>3</sup>

- Contribute to a comfortable<sup>4</sup> working environment with water-based HP Latex Ink technology
- Differentiate your business with environmental certifications<sup>3</sup>—including UL ECOLOGO®<sup>5</sup> and
- Access the most sensitive spaces with odorless prints<sup>4</sup> and compatibility with a wide range of alternative substrates.
- Reduce your plastics consumption with cartonbased cartridge<sup>8</sup> and labelless supplies; free recycling via HP Planet Partners."

## For more information, please visit http://www.hp.com/go/latex800series

## Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at https://lkc.hp.com/

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

Whitest white based on ISO/DIS 23498 compared to competitive alternatives using solvent and UV technologies under \$50,000 USD as of May, 2020. Test performed on black opaque self-adhesive vinyl (L\*:4.16 – a:0.48-b:2,34) with 160% UF printmode using HP 873 3-liter White Latex Ink Cartridge. Visual opacity = 91%.

<sup>&</sup>lt;sup>2</sup> Outdoor mode (Banner) 4-pass, 100%. Based on internal HP testing in September 2020 on Avery 3001. Print speed may vary due to the adaptive printing mechanism to avoid image quality defects.

<sup>3</sup> Based on internal competitive analysis with public information. Applicable to HP Latex technology compared to competitive large format printing alternatives using solvent and UV technologies. See individual product

data sheets for more information at https://hp.com/go/latex

Applicable to HP Latex Inks. Based on sensory evaluations conducted by Odournet, done according to VDI Guideline 3882 where 832 and 873 inks were characterized as "weak" in odor intensity and "neutral" for hedonic tone. There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

<sup>5</sup> UL ECOLOGO® Certified HP 832, HP 872, HP 873, and 882 Latex lnks and HP 864, 865, 865, 866, 867, 869, and 870 PageWide XL lnks meet a range of stringent human health and environmental considerations. Verified as of the publishing date in September 2023. For more details, please refer to the UL ECOLOGO® database at https://spot.ul.com/main-app/products/catalog/ or see https://www.ul.com/EL <sup>6</sup> Applicable to select HP Latex printers. EPEAT registered where applicable/supported. See https://epeat.net for registration status by country.

7 HP applications experts have evaluated the catalog of media listed in the HP Media Locator based on internal criteria to identify those that provide alternative solutions with certain environmental benefits compared to

the typical media within the same application type. The information in media locator is provided by the media substrate vendors. HP is not responsible for the veracity of the information from third-party companies published on the HP website. See https://www.hp.com/go/mediasolutionslocator

Applicable to HP 832. Plastic reduction based on moving from plastic ink cartridge to cardboard ink cartridges, with annual manufacturing saving of 33 tons of plastic based on average units of HP 831 and HP 831A ink cartridges from 2018 to 2020

Program availability varies. For details, see https://hp.com/hprecycle

## **Technical specifications**

Print	
Printing modes	122 m²/hr - Max Speed (1-pass) 36 m²/hr - High Speed (4-pass) 25 m²/hr - Production Fast (6-pass) 20 m²/hr - Production Fast (6-pass) 17 m²/hr - High Saturation (12-pass) 17 m²/hr - High Saturation Backlits and Backlits (8-pass) 17 m²/hr - High Saturation Backlits and Textiles (14-pass) 17 m²/hr - White Spot (60%) 3 m²/hr - White Overflood (60%) 3 m²/hr - White Underflood (100%) 2 m²/hr - 3 Layers Day & Night (160%)
Print resolution	Up to 1200 x 1200 dpi
Ink types	Water-based HP Latex Inks
Ink cartridges	9 (black, cyan, light cyan, light magenta, magenta, yellow, white, HP Latex Optimizer, HP Latex Overcoat)
Cartridge size	3L
Printheads	10 (2 cyan/black, 2 magenta/yellow, 2 light cyan/light magenta, 2 white, 1 HP Latex Optimizer, 1 HP Latex Overcoat)
Long-term print-to-print repeatability	95% of colors ≤ 1.5 dE2000 <sup>2</sup>
Media	
Handling	Roll feed, take-up reel, wiper roller <sup>3</sup> , media saver, automatic horizontal cutter (for vinyl, banner and canvas <sup>4</sup> , paper-based media, and film)
Media types	Banners, self-adhesive vinyls, films, fabrics, papers, wall coverings, canvas, synthetics, mesh, textiles <sup>5</sup>
Roll size	419 to 1625-mm rolls (580 to 1625-mm rolls with full support)
Maximum roll weight	55 kg
Maximum roll diameter	250 mm
Thickness	Up to 0.5 mm
Applications	Banners; Displays; Exhibition and event graphics; Exterior signage; Indoor posters; Interior decoration; Light boxes - film; Light boxes - paper; Murals; POP/POS; Posters; Textile; Vehicle graphics; Window graphics; Stickers
Connectivity	
Interfaces	Gigabit Ethernet (1000Base-T)
Dimensions (W x D	0xH)
Printer	2583 x 866 x 1402 mm
Shipping	2753 x 1100 x 1666 mm
Operating area	2793 x 2100 mm
Weight	
Printer	300 kg
Shipping	443 kg
What's in the box	HP Latex 800 W Printer, printheads, maintenance cartridge, printer stand, take-up reel, media feed accessory, user maintenance kit, edge holders, quick reference guide, documentation software, power cords, air purgers, 2-in spindle adaptor
Environmental ran	iges
Operating temperature	15 to 30°C
Operating humidity	20 to 80% RH (non-condensing)
Acoustics	
Sound pressure	60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)
Sound power	7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep)
Power	
Consumption	1.5-2.5 kW (5 kW peak) (printing), 105 W (ready), <4.7 W <sup>6</sup> (sleep) (<24 W <sup>7</sup> with DFE), <0.25 W (off)
Requirements	Input voltage (auto ranging) 200-240 V ( $\pm 10\%$ ) two wires and PE; 50/60 Hz ( $\pm 3$ Hz); two power cords; 16 A max per power cord
Certification	
Safety	IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC)
Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC)
Environmental	ENERGY STAR®, ROHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, UL ECOLOGO
Warranty	One-year limited hardware warranty

## **Ordering information**

### Product

3XD61B	HP Latex 800 W Printer
Accessories	
21V10A 7F3Y3A 7HR16A 7HR18A T7U73A	HP Latex 600/700/800 User Maintenance Kit HP Latex 700/800 Output Platen Protector Accessory HP Latex 700/800 Textile Kit Accessory HP Latex 700/800 In Kolletor Foams Kit HP Latex 700/800 In Kolletor Foams Kit HP Latex 500/700/800 Wiper Roller

## Original HP printing supplies

4UV97A HP 836 Light Cyan/Light Magenta Latex Printhead 4UV98A HP 836 Overcoat Latex Printhead	4UU93A 4UU94A 4UV38A 4UV39A 4UV41A 4UV41A 4UV62A 4UV88A 4UV89A 4UV89A 4UV90A 4UV91A 4UV95A	HP 836 White Latex Printhead HB 836 Optimizer Latex Printhead HB 8379 3-liter Black Latex Ink Cartridge HB 873Y 3-liter Flack Latex Ink Cartridge HB 873Y 3-liter Augenta Latex Ink Cartridge HB 873Y 3-liter White Latex Ink Cartridge HB 8733 3-liter White Latex Ink Cartridge HB 8733 3-liter White Latex Ink Cartridge HB 8733 3-liter Light Cyan Latex Ink Cartridge HB 8733 3-liter Optimizer Latex Ink Cartridge HB 8733-liter Optimizer Latex Ink Cartridge HB 8733-liter Optimizer Latex Ink Cartridge HB 8736 Black/Cyan Latex Printhead
4UV98A HP 836 Overcoat Latex Printhead	4UV96A 4UV97A	HP 836 Magenta/Yellow Latex Printhead HP 836 Light Cyan/Light Magenta Latex Printhead
	4UV98A	HP 836 Overcoat Latex Printhead

### Original HP large format printing materials

- HP PVC-free Wallpaper (UL GREENGUARD GOLD Certified<sup>8</sup>, FSC<sup>®</sup> certified<sup>9</sup>, meets AgBB criteria<sup>10</sup>) HP Photo-realistic Poster Paper HP Premium Satin Carwas HP Prime Match & if GP (REACH compliant<sup>11</sup>) HP Prime Match & if GP (REACH compliant<sup>11</sup>) HP Premium Removable Gloss Adhesive Vinyl (REACH compliant<sup>11</sup>)

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

#### Service and Support

- U13DDE HP 2 year Next Business Day with Defective Media Retention
  U13DDE HP 3 year Next Business Day with Defective Media Retention
  U13DMPE HP 1 year Post Warranty Next Business Day with Defective Media Retention
  U13DTPE HP 2 year Post Warranty Next Business Day with Defective Media Retention
- Print speeds may vary due to the adaptive printing mechanism to avoid image quality defects.
  The color variation between printing has been measured at 12 pass mode on viryl media. Reflective measurements on a 943 color target under CE standard Illuminant DSO, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E-2012. 5% of colors may experience variations above 1.5 dE2000. Backlit substrates measured in transmission mode may yield different results.

  Wiper roller is an optional accessory.
  Automatic horizontal cutter is for use with thinner banners and canvas only. It is recommended to perform a test.
  Fattlie Rt Accessory required for long runs of textile and porous textile.
  Esculding Type 2 DFE (Digital Front End) as defined in Energy Star® Product Specification for Imaging Equipment version 3.1.
  Total power measured in sleep mode including the Digital Front End contained on the product.
  But GREENGUARD Gold Certification to Ut. 2818 demonstrates that products are certified to Ut.S GREENGUARD standards for low chemical emissions into Indoor air during product usage. For more information, visit http://www.ut.com/lgg or http://www.greenguard.org
  Trademark license code FSC-C115319.
  With HP Latex Inks, prints meet AgBB criteria for health-related evaluation of VOC emissions. See http://umweltbundesamt.defen/topics/health/commissions-working-groups/committee-for-health-related-evaluation-of-building

- evaluation-or-building

  "1" This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive
  published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products,
  see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.

























